

AlCaDB Workshop on Run 2017 preparation – Pixel talk

Tamás Álmos VÁMI¹ for the Pixel group

¹ Wigner RCP, Budapest



AlCaDB workshop





Preparation of
2017 data taking

The New Phase I Pixel Detector

4 layers and 3-3 disks allow us better tracking, vertex reconstruction and b-tag efficiency

Digital readout with increased buffer sizes thus we can expect nearly 100% efficiency

Similar sensor with slightly better resolution in BPix (smaller pixel threshold) and much better in FPix



Pixel plan for 2017 running

BPIX/FPIX installation by the beginning of March

Commissioning and online calibration by the beginning of April

In the beginning of the data taking in June detector alignment and standard set of calibrations and checks

Part of the calibration can be done (less accurately) with cosmics (in April)

Calibrations

In the beginning of data taking in around June, we plan to

Fine tune the **timing** of the detector using the first collisions

--> 1 day is needed

High Voltage Bias scan to validate the voltage settings

Measure the Lorentz Angle and update the Templates, GenErrors

This could trigger an update in the payloads

Measure and validate that the resolution is as good as expected

Calibrations

Monitoring during the year

In the beginning of **each data-taking period**, we measure **LA**, **hit efficiency**, **resolution**, and check if performance is as expected → update certain payloads if needed (expected about 5 times in a year)

Check the performance of the **simulation** against data and tune it if needed

Inefficiencies will be added when needed (although detector is designed to easily handle $2e34$ instantaneous luminosities)

Calibrations

Later during the year

Occasional HV Scans

- Depending on the integrated lumi voltage might be raised
- (similar to the beginning of Run II)

Raising the voltage may only happen in 2018 if the integrated luminosity is not too great

Calibrations

Pixel Calibration Workflows twiki

<https://twiki.cern.ch/twiki/bin/viewauth/CMS/PixelCalibrationWorkflows>

Pixel DB Tags twiki

<https://twiki.cern.ch/twiki/bin/view/CMS/PixelDBTags>

Main Pixel tools software repository:

<https://github.com/cms-analysis/DPGAnalysis-SiPixelTools>


First in-situ
measurement &
2017 operations

HV scan

The efficiency for the hits on track measured for different bias voltages → if silicon is fully depleted, hit efficiency reaches plateau

If short with time, HV scan might be skipped as sensors are new and known

Change in the HV settings leads to new LA/GenErr/Template payloads, too



During the data taking


- Perform occasional HV scans
- Raise voltage if/when needed

Gain calibration

ADC to Vcal conversion

The gain and pedestals are extracted from a fit in the low VCal region for each pixel separately

This calibration doesn't require collisions and is done online while running in local
Then it is analysed **offline**



During the data taking


- Every few weeks, but
- DB update at the technical stops
- Or if offline monitoring justifies it

Lorentz Angle Calibrations

Measurements procedure:

- **Barrel** – we use muons from collisions data (/MuOnia/ dataset) for the minimum clusters size method
- **Forward** – In Run I we mainly used Cosmic muons for the grazing angle method
- In both cases, we analyze the data **offline**

LA also strongly depend on accumulated **radiation dose** thus we need to measure and upload calibration constants regularly



During the data taking


- 5-10 times per year

Templates

Template hit reconstruction:

- Yields a better estimate of the **cluster parameters** than that used in generic hit reconstruction
- Is needed by the alignment that measures the final values of the **Lorentz Angles** that are uploaded into the DB

- We analyze the same dataset **offline** that we use for the Lorentz Angle measurements (also using MuOnia)
- The templates are created with a simulation that uses our Lorentz Angle measurements and is needed for the final ReReco



During the data taking

- DB update at the technical stops


SiPixelQuality – List of Bad Components

List of dead modules/readout chips of the detector
Problems we encountered in Run I:

- Broken parts (wire-bonds, VAna sense wire)
- Problem with the fiber extension cable
- Temporary issues with old readout chips

During the data taking

- DB update anytime needed



DB side of the payloads

Record names (Data)

SiPixelGainCalibrationOfflineRcd
SiPixelGainCalibrationForHLTRcd

SiPixelLorentzAngleRcd
SiPixelTemplateDBObjectRcd
SiPixelGenErrorDBObjectRcd

SiPixelQualityRcd
SiPixelFedCablingMapRcd

Record names (Simulation)

SiPixelGainCalibrationOfflineSimRcd
SiPixelGainCalibrationForHLTSimRcd

SiPixelLorentzAngleSimRcd
SiPixelTemplateDBObjectRcd
SiPixelGenErrorDBObjectRcd

SiPixelQualityRcd
SiPixelFedCablingMapRcd

Scenarios for
MC Simulations
and datasets used

Scenarios for MC Simulations

Dynamic Efficiency loss can be simulated
(but first we need to collect data)

Different parts of the detector fail → Failure Scenarios study

The validation plots of study can be found in a presentation from me at the Pixel Offline meeting:

<https://indico.cern.ch/event/607513/#29-pixel-failure-scenarios>

Datasets

No ALCARECO datasets are used by us

MuOnia dataset for LA and Template/GenErr studies


ZeroBias RAW dataset for Timing/HV/SiPixelQuality

Backup

Timing scan

Optimal setting of pixel detector clock vs LHC clock must be determined using first collisions:

- **Coarse time alignment** (WBC finding) with DQM dedicated online client is being prepared
- **Fine tuning** with DQM and offline analysis (efficiency and cluster size/charge)



During the data taking:
not planned